

Price bid/ BOQ

NAME OF WORK: Repairing of damaged floors and electrical wiring works of office building campus of O/o the AGM, Nagaon T&T division, Samaguri and Painting on roof sheets of O/o the AGM, Nagaon T&T division, Samaguri, AEGCL

Name of the bidder.....

NIT No- AEGCL/DGM/TTC/TEZ/T-20/2026/312 Date 07/01/2025

SL NO	DESCRIPTIONS OF ITEMS	QNTY	UNIT	RATE(Rs.)	AMOUNT(Rs.)
1	Demolishing cement concrete manually/ by mechanical means including disposal of material within 50 metres lead as per direction of Engineer - in - charge. Nominal concrete 1:4:8 or leaner mix (i/c equivalent design mix)	0.64	cum		
2	Cement concrete flooring 1:2:4 (1 cement : 2 coarse sand : 4 graded stone aggregate) finished with a floating coat of neat cement, including cement slurry, but excluding the cost of nosing of steps etc. complete. 40 mm thick with 20 mm nominal size stone aggregate	15.96	cum		
3	Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete.	36.96	sqm		
4	Applying one coat of water thinnable cement primer of approved brand and manufacture on wall surface : Water thinnable cement primer	36.96	sqm		
5	Wall painting with acrylic emulsion paint of approved brand and manufacture to give an even shade : Two or more coats on new work	36.96	sqm		
6	Painting with synthetic enamel paint of approved brand and manufacture to give an even shade : Two or more coats on new work	32.04	sqm		
7	Providing and fixing brass curtain rods of wall thickness 1.25 mm with two brass brackets fixed with brass screws and wooden plugs etc. wherever necessary complete. 20 mm diameter.	6.40	metre		
8	Wiring for light/ fan/ call bell point with 2x1.5 sq mm P.V.C. insulated single core unsheathed industrial (Multistrand) cable FR conforming to IS-694: 1990 with flexible bright annealed electrolytic copper conductor for voltage grade up to 1100 volts (Finolex /RR Kabel /Nicco / Anchor or Equivalent Make as approved by the Deptt.) with flat 19 mm ISI marked casing 'n' capping (AKG / Precision/ Presto Plast/Polycab/ MW or equivalent make as approved by the Deptt.) in surface system, including 6 Amp flush type switch/ bell push (Anchor Penta/Gold medal /Kolor kany.Kom/ Havells or equivalent make as approved by the Deptt.) GI/ MS switch board (ISI marked) half conceal on wall with phenolic laminated sheet cover ,ceiling rose (Anchor/Gold medal /Kolor kany.Kom / Havells or equivalent make as approved by the Deptt.) etc. complete as directed and specified by the Deptt. Medium point up to 6.00 metre. Length.	28	Each		

9	Wiring for light/ fan/ call bell point with 2x1.5 sq mm P.V.C. insulated single core unsheathed industrial (Multistrand) cable FR conforming to IS-694: 1990 with flexible bright annealed electrolytic copper conductor for voltage grade up to 1100 volts (Finolex /RR Kabel /Nicco / Anchor or Equivalent Make as approved by the Deptt.) with flat 19 mm ISI marked casing 'n' capping (AKG / Precision/ Presto Plast/Polycab/ MW or equivalent make as approved by the Deptt.) in surface system, including 6 Amp flush type switch/ bell push (Anchor Penta/Gold medal /Kolor kany.Kom/ Havells or equivalent make as approved by the Deptt.) GI/ MS switch board (ISI marked) half conceal on wall with phenolic laminated sheet cover ,ceiling rose (Anchor/Gold medal /Kolor kany.Kom / Havells or equivalent make as approved by the Deptt.) etc. complete as directed and specified by the Deptt. Long point up to 10.00 metre. Length.	20	Each	
10	Wiring to 5 a pin 6 Amps plug point with 1.5 sq. mm P.V.C. insulated single core unsheathed industrial (Multistrand) cable FR conforming to IS-694: 1990 with flexible bright annealed electrolytic copper conductor for voltage grade up to 1100 volts (Finolex /RR Kabel /Nicco / Anchor or Equivalent Make as approved by the Deptt.) with flat 19 mm ISI marked casing 'n' capping (AKG / Precision/ Presto Plast/Polycab/ MW or equivalent make as approved by the Deptt.) in surface system, including 5 pin 6 Amps flush type plug socket and 6 Amps F/T switch (Anchor penta /Gold medal /Kolor kany.Kom/Havells or equivalent make as approved by the Deptt.), GI/ MS switch board (I.S.I. marked) with phenolic laminated sheet cover including earth continuity with 1.5 sq. mm. cable to third pin of the plug socket etc. as required complete, when placed elsewhere. Medium point up to 6.00 metre. Length.	8	Each	
11	Wiring for 5/6 pin 16 Amps power plug point with 4 sq. mm. P.V.C. insulated single core unsheathed industrial (Multistrand) cable FR conforming to IS-694: 1990 with flexible bright annealed electrolytic copper conductor for voltage grade up to 1100 volts (Finolex /RR Kabel /Nicco / Anchor or Equivalent Make as approved by the Deptt.) with flat 19 mm ISI marked casing 'n' capping (AKG / Precision/ Presto Plast/Polycab/ MW or equivalent make as approved by the Deptt.) in surface system, including providing and fixing 5/6 pin 16 Amps flush type socket outlets and 16 Amps flush type switch (Anchor penta /Gold medal /Kolor kany.Kom/Havells or equivalent make as approved by the Deptt.),GI/ MS switch board (I.S.I. marked) with phenolic laminated sheet cover earth continuity with 2.5 sq. mm cable to the 3rd pin of the socket as required complete.Medium point up to 6.00 metre. Length.	38	Each	
12	Wiring for drawing sub-main line with P.V.C. insulated single core unsheathed industrial (Multistrand) cable FR conforming to IS-694: 1990 with flexible bright annealed electrolytic copper conductor for voltage grade up to 1100 volts (Finolex /RR Kabel /Nicco / Anchor or Equivalent Make as approved by the Deptt.) in surface flat ISI marked casing 'n' capping (AKG / Precision/ Presto Plast/Polycab/ MW or equivalent make as approved by the Deptt.) system including earth continuity. With 2 x 2.5 sq. mm. + earth continuity with 1x1.5 sq. mm. in flat 19 mm ISI marked casing 'n' capping system.	60.00	RM	

13	Supplying fixing I.C.T.P and N link Main Switch with rewireable fuses of 500 Volt grade(HPL/ GECO / ANCHOR or equivalent make) including drilling boards/iron frames and fixing with bolts and nuts and connection as approved by the Deptt.)complete as required. 30/32 Amps Capacity T.P.N	1	Each		
14	Supplying with fitting and fixing single Pole 10 KA 240/415V 50Hz MCB of the following capacity complete with making necessary connection as approved, specified and directed by the deptt. B Series ---- 10 A (Schneider MG, legrand, Hager make)	10	Each		
15	Supplying with fitting and fixing sheet steel, phosphatised, powder painted Single door surface mounting MCCB enclosure of the following rating MCCB fitted on wall with grouting nuts & bolts as reqd. complete with making necessary connection as approved, specified and directed by the deptt. ABB, Schneider MG, legrand, Hager make for 100A 3P/4P MCCB	1	Each		
16	Supplying including fitting fixing of following A.C. Exhaust fan in the existing hole on the wall of following sweeps with making necessary connection as approved by the Deptt.)as required complete and as directed by the Department. High Speed 225 mm sweep (ORIENT make), Trans Air 225 mm sweep (Crompton make), Ventil Air DX 250 mm sweep Louver type (Havells make).	2	Each		
17	Supplying and fixing of Call bell (Buzzer) including 6 amp capacity flush type bell push switch including connection as approved by the Deptt.)as required.	15	Each		
18	Supplying and fixing of Plain Pendent holder (Anchor Penta PC CHERRY /Gold medal /Kolor kany.kom/Havells or equivalent make as approved by the Deptt.) with twin twisted flexible cord including connection as approved by the Deptt.)complete Without Lamp	24	Each		
19	Supplying fitting and fixing of ceiling fan regulator including connections etc. complete as required. Electronic Type	9	Each		
20	Supplying and fitting of 18/20 Watt CFL/LED lamp in the existing batten holder/angle holder/decorative bracket/bulk head fitting/ pendent holder etc. as specified and directed by the deptt.	10	Each		
21	Removing dry or oil bound distemper, water proofing cement paint and the like by scrapping, sand papering and preparing the surface smooth including necessary repairs to scratches etc. complete.	326.00	Sqm		
22	Applying priming coat:With ready mixed red oxide zinc chromate primer of approved brand and manufacture on steel galvanised iron/ steel works .	326.00	Sqm		
23	Painting on G.S. sheet with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade :Two coats	326.00	Sqm		
	Total Excluding GST=				
	Add 18% GST=				
	Grand Total (inclusive of GST)=				