

**Financial Bid/BOQ**

**NAME OF WORK: Renovation and Repairing of existing damaged quarter to be converted into O/o the GM, CAZ, AEGCL, Nagaon at 220/132/33 KV GSS, AEGCL, Samaguri.**

**NIT No:-AEGCL/DGM/TTC/TEZ/T-20/2023-24/196 Dated: 12/05/2023**

**Name of the bidder:.....**

| <b>SL NO</b> | <b>DESCRIPTIONS OF ITEMS</b>  | <b>QUANTITY</b> | <b>UNIT</b> | <b>UNIT RATE(Rs.)</b> | <b>AMOUNT(Rs.)</b> |
|--------------|---|-----------------|-------------|-----------------------|--------------------|
| <b>1</b>     | Demolishing cement concrete manually/ by mechanical means including disposal of material within 50 metres lead as per direction of Engineer - in - charge.<br>15.2.2 Nominal concrete 1:4:8 or leaner mix (i/c equivalent design mix) | <b>3.47</b>     | <b>cum</b>  |                       |                    |
| <b>2</b>     | Demolishing brick work manually/ by mechanical means including stacking of serviceable material and disposal of unserviceable material within 50 metres lead as per direction of Engineer-in-charge.<br>15.7.4 In cement mortar       | <b>5.22</b>     | <b>cum</b>  |                       |                    |
| <b>3</b>     | Dismantling doors, windows and clerestory windows (steel or wood) shutter including chowkhats, architrave, holdfasts etc. complete and stacking within 50 metres lead :<br>15.12.1 Of area 3 sq. metres and below                     | <b>10.00</b>    | <b>Each</b> |                       |                    |
| <b>4</b>     | Dismantling wood work in frames, trusses, purlins and rafters up to 10 metres span and 5 metres height including stacking the material within 50 metres lead :<br>15.14.1 Of sectional area 40 square centimetres and above           | <b>0.18</b>     | <b>cum</b>  |                       |                    |
| <b>5</b>     | Dismantling cement asbestos or other hard board ceiling or partition walls including stacking of serviceable materials and disposal of unserviceable materials within 50 metres lead.   | <b>17.28</b>    | <b>sqm</b>  |                       |                    |
| <b>6</b>     | Dismantling W.C. Pan of all sizes including disposal of dismantled materials i/c malba all complete as per directions of Engineer-in-Charge.  | <b>2.00</b>     | <b>Each</b> |                       |                    |

|           |   |              |            |  |  |
|-----------|---|--------------|------------|--|--|
| <b>7</b>  | Providing and laying in position cement concrete of specified grade<br>excluding the cost of centering and shuttering - All work up to plinth level :<br>4.1.5 1:3:6 (1 Cement : 3 coarse sand (zone-III) derived from natural sources : 6 graded stone aggregate 20 mm nominal size derived from natural sources)        | <b>9.07</b>  | <b>cum</b> |  |  |
| <b>8</b>  | Half brick masonry with common burnt clay F.P.S. (non modular) bricks<br>of class designation 7.5 in superstructure above plinth level up to floor<br>V level.<br>6.13.2 Cement mortar 1:4 (1 cement :4 coarse sand)  | <b>25.06</b> | <b>sqm</b> |  |  |
| <b>9</b>  | Cement concrete flooring 1:2:4 (1 cement : 2 coarse sand : 4 graded stone aggregate) finished with a floating coat of neat cement, including cement slurry, but excluding the cost of nosing of steps etc. complete.<br>11.3.1 40 mm thick with 20 mm nominal size stone aggregate  | <b>86.78</b> | <b>sqm</b> |  |  |
| <b>10</b> | Steel reinforcement for R.C.C. work including straightening, cutting, bending, placing in position and binding all complete above plinth level.<br>5.22A.1 Mild steel and Medium Tensile steel bars   | <b>8.54</b>  | <b>kg</b>  |  |  |
| <b>11</b> | Providing and laying in position specified grade of reinforced cement concrete, excluding the cost of centering, shuttering, finishing and reinforcement<br>5.1.2 1:1.5:3 (1 cement : 1.5 coarse sand (zone-III) derived from natural sources : 3 graded stone aggregate 20 mm nominal size derived from natural sources) | <b>0.17</b>  | <b>cum</b> |  |  |
| <b>12</b> | Centering and shuttering including strutting, propping etc. and removal of form for<br>5.9.1 Foundations, footings, bases of columns, etc. for mass concrete  | <b>2.32</b>  | <b>sqm</b> |  |  |

|           |  |              |              |  |  |
|-----------|--|--------------|--------------|--|--|
| <b>13</b> | <p>Providing and fixing Ist quality ceramic glazed wall tiles conforming to IS: 15622 (thickness to be specified by the manufacturer), of approved make, in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer-in-Charge, in skirting, risers of steps and dados, over 12 mm thick bed of cement mortar 1:3 (1 cement : 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per sqm, including pointing in white cement mixed with pigment of matching shade complete.</p> | <b>52.17</b> | <b>sqm</b>   |  |  |
| <b>14</b> | <p>Providing and laying vitrified floor tiles in different sizes (thickness to be specified by the manufacturer) with water absorption less than 0.08% and conforming to IS: 15622, of approved make, in all colours and shades, laid on 20mm thick cement mortar 1:4 (1 cement : 4 coarse sand), jointing with grey cement slurry @ 3.3 kg/ sqm including grouting the joints with white cement and matching pigments etc., complete.<br/>11.41.1 Size of Tile 500x500 mm</p>   | <b>47.34</b> | <b>sqm</b>   |  |  |
| <b>15</b> | <p>13.7 12 mm cement plaster finished with a floating coat of neat cement of 13.7.2 1:4 (1 cement: 4 fine sand)</p>  | <b>50.12</b> | <b>sqm</b>   |  |  |
| <b>16</b> | <p>Providing ridges or hips of width 60 cm overall width plain G.S. sheet fixed with polymer coated J or L hooks, bolts and nuts 8 mm dia G.I. limpet and bitumen washers complete.<br/>12.4.2 0.63 mm thick with zinc coating not less than 275 gm/m<sup>2</sup></p>  | <b>20.00</b> | <b>meter</b> |  |  |

|    |   |       |       |  |  |
|----|---|-------|-------|--|--|
| 17 | <p>Providing corrugated G.S. sheet roofing including vertical / curved surface fixed with polymer coated J or L hooks, bolts and nuts 8 mm diameter with bitumen and G.I. limpet washers or with G.I. limpet washers filled with white lead, including a coat of approved steel primer and two coats of approved paint on overlapping of sheets complete (up to any pitch in horizontal/ vertical or curved surfaces), excluding the cost of purlins, rafters and trusses and including cutting to size and shape wherever required.<br/>12.1.3 0.63 mm thick with zinc coating not less than 275 gm/ m<sup>2</sup></p> | 98.64 | sqm   |  |  |
| 18 | <p>Providing and fixing fibre cement reinforced by organic fibres and/or inorganic synthetic fibres roofing accessories in all colours with polymer coated J or L hooks, bolts and nuts and or G.I. seam bolts and nuts, G.I. plain and bitumen washers or with self drilling fastener and EPDM washer etc. complete:<br/>12.13.5 Barge boards</p>  | 50.00 | metre |  |  |
| 19 | <p>Providing wood work in frames of doors, windows, clerestory windows and other frames, wrought framed and fixed in position with hold fast lugs or with dash fasteners of required dia &amp; length (hold fast lugs or dash fastener shall be paid for separately).<br/>9.1.3 Kiln seasoned and chemically treated hollock wood</p>   | 0.85  | cum   |  |  |
| 20 | <p>Providing and fixing 35 mm thick factory made laminated veneer lumber door shutter conforming to IS : 14616 and TADS 15:2001 (Part B), fixing with butt hinges of required size with necessary screws, all complete as per directions of Engineer- in-charge and panelling with panels of :<br/>9.6.1 12 mm thick plain grade -1, medium density flat pressed three layer particle board FPT - I or graded wood particle board FPT- I, IS : 3087 marked, bonded with BWP type synthetic resin adhesive as per IS : 848 :</p>   | 16.17 | sqm   |  |  |

|    |  |        |      |  |  |
|----|--|--------|------|--|--|
| 21 | <p>Providing and fixing factory made panel PVC door shutter consisting of frame made out of M.S. tubes of 19 gauge thickness and size of 19 mm x 19 mm for styles and 15x15 mm for top &amp; bottom rails. M.S. frame shall have a coat of steel primers of approved make and manufacture. M.S. frame covered with 5 mm thick heat moulded PVC 'C' channel of size 30 mm thickness, 70 mm width out of which 50 mm shall be flat and 20 mm shall be tapered in 45 degree angle on both side forming styles and 5 mm thick, 95 mm wide PVC sheet out of which 75mm shall be flat and 20 mm shall be tapered in 45 degree on the inner side to form top and bottom rail and 115 mm wide PVC sheet out of which 75 mm shall be flat and 20 mm shall be tapered on both sides to form lock rail. Top, bottom and lock rails shall be provided both side of the panel. 10 mm (5 mm x 2 ) thick, 20 mm wide cross PVC sheet be provided as gap insert for top rail &amp; bottom rail, paneling of 5 mm thick both side</p> <p><del>PVC sheet to be fitted in the M.S. frame welded/cooled to</del></p> | 5.04   | sqm  |  |  |
| 22 | <p>Providing and fixing aluminium sliding door bolts, ISI marked anodised (anodic coating not less than grade AC 10 as per IS : 1868), transparent or dyed to required colour or shade, with nuts and screws etc. complete : 9.96.1 300x16 mm</p>  | 4.00   | each |  |  |
| 23 | <p>Renewing glass panes and refixing existing wooden fillets:<br/>14.7.1 Float glass panes of nominal thickness 4 mm (weight not less than 10kg/sqm)</p>   | 3.00   | sqm  |  |  |
| 24 | <p>Removing dry or oil bound distemper, water proofing cement paint and the like by scrapping, sand papering and preparing the surface smooth including necessary repairs to scratches etc. complete.</p>  | 375.78 | sqm  |  |  |
| 25 | <p>Finishing walls with water proofing cement paint of required shade :<br/>13.109.1 Old work (one or more coats applied @ 2.20 kg/10 sqm)<br/>over priming coat of primer applied @ 0.80 litres/10 sqm complete including cost of Priming coat.</p>   | 375.78 | sqm  |  |  |

|           |   |               |             |  |  |
|-----------|---|---------------|-------------|--|--|
| <b>26</b> | Painting on G.S. sheet with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade :<br>Old work (two coats)   | <b>136.44</b> | <b>sqm</b>  |  |  |
| <b>27</b> | Painting with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade :<br>13.99.1 One or more coats on old work  | <b>152.58</b> | <b>sqm</b>  |  |  |
| <b>28</b> | Providing and fixing water closet squatting pan (Indian type W.C. pan ) with 100 mm sand cast Iron P or S trap, 10 litre low level white P.V.C. flushing cistern, including flush pipe, with manually controlled device (handle lever) conforming to IS : 7231, with all fittings and fixtures complete, including cutting and making good the walls and floors wherever required:<br>White Vitreous china Orissa pattern W.C. pan of size 580x440 mm with integral type foot rests | <b>2.00</b>   | <b>each</b> |  |  |
| <b>29</b> | Providing and fixing white vitreous china flat back or wall corner type lipped front urinal basin of 430x260x350 mm or 340x410x265 mm sizes respectively.   | <b>1.00</b>   | <b>each</b> |  |  |
| <b>30</b> | Providing and fixing Stainless Steel A ISI 304 (18/8) kitchen sink as per IS:13983 with C.I. brackets and stainless steel plug 40 mm, including painting of fittings and brackets, cutting and making good the walls wherever required :<br>17.10.2 Kitchen sink without drain board<br>17.10.2.3 470x420 mm bowl depth 178 mm  | <b>1.00</b>   | <b>each</b> |  |  |
| <b>31</b> | Providing and fixing wash basin with C.I. brackets, 15 mm C.P. brass pillar taps, 32 mm C.P. brass waste of standard pattern, including painting of fittings and brackets, cutting and making good the walls wherever require:<br>17.7.2 White Vitreous China Wash basin size 630x450 mm with a single 15 mm C.P. brass pillar tap  | <b>3.00</b>   | <b>each</b> |  |  |
| <b>32</b> | 18.15 Providing and fixing brass bib cock of approved quality :<br>18.15.1 15 mm nominal bore   | <b>6.00</b>   | <b>each</b> |  |  |
| <b>33</b> | Providing and fixing brass stop cock of approved quality :<br>18.16.1 15 mm nominal bore  | <b>2.00</b>   | <b>each</b> |  |  |

|           |   |              |              |  |  |
|-----------|---|--------------|--------------|--|--|
| <b>34</b> | Providing and fixing C.P. brass shower rose with 15 or 20 mm inlet :<br>18.22.1 100 mm diameter   | <b>1.00</b>  | <b>each</b>  |  |  |
| <b>35</b> | Providing and fixing mirror of superior glass (of approved quality) and of required shape and size with plastic moulded frame of approved make and shade with 6 mm thick hard board backing :<br>17.32.1 Circular shape 450 mm dia  | <b>3.00</b>  | <b>each</b>  |  |  |
| <b>36</b> | Providing and fixing PTMT towel ring trapezoidal shape 215 mm long, 200 mm wide with minimum distances of 37 mm from wall face with concealed fittings arrangement of approved quality and colour, weighing not less than 88 gms.   | <b>3.00</b>  | <b>each</b>  |  |  |
| <b>37</b> | Providing and fixing PTMT soap Dish Holder having length of 138mm, breadth 102mm, height of 75mm with concealed fitting arrangements, weighing not less than 106 gms.   | <b>3.00</b>  | <b>each</b>  |  |  |
| <b>38</b> | Providing and fixing white vitreous china pedestal type water closet (European type W.C. pan) with seat and lid, 10 litre low level white P.V.C. flushing cistern, including flush pipe, with manually controlled device (handle lever), conforming to IS : 7231, with all fittings and fixtures complete, including cutting and making good the walls and floors wherever required :<br>17.2.1 W.C. pan with ISI marked white solid plastic seat and lid | <b>1.00</b>  | <b>each</b>  |  |  |
| <b>39</b> | Providing and fixing 8 mm dia C.P. / S.S. Jet with flexible tube upto 1 metre long with S.S. triangular plate to European type W.C. of quality and make as approved by Engineer - in - charge.  | <b>1.00</b>  | <b>each</b>  |  |  |
| <b>40</b> | Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, having thermal stability for hot & cold water supply, including all CPVC plain & brass threaded fittings, including fixing the pipe with clamps at 1.00 m spacing. This includes jointing of pipes & fittings with one step CPVC solvent cement and testing of joints complete as per direction of Engineer in Charge.<br>18.7.3) 25 mm nominal dia Pipes                               | <b>10.00</b> | <b>metre</b> |  |  |
|           | 18.7.1) 15 mm nominal dia Pipes   | <b>30.00</b> | <b>metre</b> |  |  |

|    |  |       |       |  |  |
|----|--|-------|-------|--|--|
| 41 | <p>Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, having thermal stability for hot &amp; cold water supply including all CPVC plain &amp; brass threaded fittings This includes jointing of pipes &amp; fittings with one step CPVC solvent cement, trenching, refilling &amp; testing of joints complete as per direction of Engineer in Charge.</p> <p>External work<br/>18.9.9 100 mm nominal dia Pipes</p>  | 15.00 | metre |  |  |
| 42 | <p>Wiring for light/ fan/ call bell point with 2x1.5 sq mm P.V.C. insulated single core unsheathed industrial (Multistrand) cable FR conforming to IS-694: 1990 with flexible bright annealed electrolytic copper conductor for voltage grade up to 1100 volts (Finolex /RR Kabel /Nicco / Anchor or Equivalent Make as approved by the Deptt.) with flat 19 mm ISI marked casing 'n' capping (AKG / Precision/ Presto Plast/Polycab/ MW or equivalent make as approved by the Deptt.) in surface system, including 6 Amp flush type switch/ bell push (Anchor Penta/Gold medal /Kolor kany.Kom/ Havells or equivalent make as approved by the Deptt.) GI/ MS switch board (ISI marked) half conceal on wall with phenolic laminated sheet cover ,ceiling rose (Anchor/Gold medal /Kolor kany.Kom / Havells or equivalent make as approved by the Deptt.) etc. complete as directed and specified by the Deptt.</p> <p>Short point up to 3.00 metre. length.</p> | 10.00 | Each  |  |  |
|    | Medium point up to 6.00 metre. Length.   | 14.00 | each  |  |  |
| 43 | <p>Wiring to 5 a pin 6 Amps plug point with 1.5 sq. mm P.V.C. insulated single core unsheathed industrial (Multistrand) cable FR conforming to IS-694: 1990 with flexible bright annealed electrolytic copper conductor for voltage grade up to 1100 volts (Finolex /RR Kabel /Nicco / Anchor or Equivalent Make as approved by the Deptt.) with flat 19 mm ISI marked casing 'n' capping (AKG / Precision/ Presto Plast/Polycab/ MW or equivalent make as approved by the Deptt.) in surface system, including 5 pin 6 Amps flush type plug socket and 6 Amps F/T switch (Anchor penta /Gold medal /Kolor kany.Kom/Havells or equivalent make as approved by the Deptt.), GI/ MS switch board (I.S.I. marked) with phenolic laminated sheet cover including earth continuity with 1.5 sq. mm. cable to third pin of the plug socket etc. as required complete, when placed elsewhere.</p> <p>1.2.1 Short point up to 3.00 metre. length.</p>                    | 10.00 | each  |  |  |



|                             |   |       |       |  |  |
|-----------------------------|---|-------|-------|--|--|
| 44                          | <p>Wiring for drawing sub-main line with P.V.C. insulated single core unsheathed industrial (Multistrand) cable FR conforming to IS-694: 1990 with flexible bright annealed electrolytic copper conductor for voltage grade up to 1100 volts (Finolex /RR Kabel /Nicco / Anchor or Equivalent Make as approved by the Deptt.) PVC conduit (Berlia/ AKG / Precision/ Presto Plast/Polycab/ MW or equivalent make as approved by the Deptt.) including earth continuity in surface/ recessed 20 mm. dia. 2mm thick/ heavy ISI marked IS: 9537 PART - III rigid PVC conduit wiring system.</p> <p>2,7.1. With 2 x 2.5 sq. mm. + earth continuity with 1x1.5 sq. mm. in 20 mm. dia. 2mm thick/ heavy rigid PVC IS: 9537 Part - III conduit.</p> | 75.00 | metre |  |  |
| 45                          | <p>Supplying with fitting and fixing single Pole 10 KA 240/415V 50Hz MCB of the following capacity complete with making necessary connection as approved, specified and directed by the deptt.</p> <p>16.1.1B Series<br/>(Schneider MG, legrand, Hager make)<br/>16.1.1.2)6 to 32A</p>  | 4.00  | each  |  |  |
| 46                          | <p>Cleaning and repairing of septic tank as directed by the deptt.</p>  | 1     | LS    |  |  |
| <b>Total Including GST=</b> |   |       |       |  |  |