BOQ/ Price Bid

Name of Work:- Repairing of floor and installation of sanitary fittings for staff hostel at 220 KV Sonabil GSS, AEGCL.

NIT No:- AEGCL/DGM/TTC/TEZ/T-20/2022/172 Dated 13/07/2022

Name of Bidder:

Sl.	Description of Item	Qnty	Unit	Rate	Amount
1	Demolishing CC floors of various thickness including top layer and base course and disposal of debris as directed for all levels.	63.26	Sqm		
	65mm thick cement concrete floor consisting 53mm under layer of cement concrete in prop (1:3:6)& 12mm thick wearing course of cement sand plastering in prop 1:2 laid in panels and finished with a flooring coat of neat cement finish.(using cement slurry for bond @2.75 kg per square mtre of floor area) including curing etc complete as directed.	43.82	Sqm		
3	Providing and fixing clear sheet glass beded in putty and fixed with/without wooden bidding including necessary cutting and glass to be required sized (payment for wooden bead shall be made separately)	1.56	Sqm		
4	Supplying, fitting anf fixing in position reinforcement bars confirming to relevant IS Code for RCC Works includining straightening, cutting, bending to proper shapes and placing them in position.	0.61	Qtl		
5	RCC work with shuttering: Providing and laying Plain/Reinforced cement concrete works cement coarse sand & 20mm down graded stone aggregate including dewatering if necessary, and curing complete but excluding cost of form work and reinforcement for reinforced cement concrete works (shuttering where necessary shall be measured and paid separately).	0.54	cum		

	Providing polished ceramic wall tiles of approved quality, size, shape and thickness not less than 8mm on walls and skirtings over cement mortar bed 10 mm thick in prop. 1:3 (1 cement : 3 coarse sand) including cutting where necessary finished with flush pointing with Fix-A-Tile (Choksey / Sika / Pedelite / Rouf) /white cement slurry mixed with approved pigment to match shade of tiles complete at all levels as specified and directed. (Cement plastering to be measured and paid separately). (Coloured pigment should be in conformity with colour of tiles and as approved and directed by the Department). (Walls means both interior and exterior walls).	105.35	Sqm	
:	Providing antiskid Tiles of approved quanlity size, shape and thickness not less than 8mm on floor, skirting over a cement mortar bed of 15mm thick in prop(1:3) approved make fix with fix-A-Tile complete at all levels specified and directed	19.44	Sqm	
:	a) Removing dry or oil bound distemper by washing and scraping and sand papering the wall surface smooth including necessary repairs to scratches complete.	59.07	Sqm	
	a) Applying one coat of cement primer of approved brand and manufacture on new wall surface after throughly brooming the surfaces free from mortar droppings and other foreign matter and including preparing the surface even and sand papered smooth.	59.07	Sqm	
	b) Finishing wall with water proofing cement paint of approved brand and manufacture and of required shade on new wall surface (two coats) to give an even shade after throughly brooming the surfaces to remove all dirt and remains of loose powdered materials.		Sqm	
]	Providing vitreous china wash basin with C.I/M.S brackets, C.P brass chain with plug 1.13.3:- Without pedestal (A) Parry ware make (a) White (i) Star basin500 x 400	6	Each	
	Providing fitting & fixing mirror with plastic frame of size 500mmx400mm complete as directed and specified (b) Size 600 x 450 mm	6	Each	

make paintii walls make. (iv) Si No. C	ingle Bowl (240x180) Flat Edge- Glossy (Cat.	6	Each	
valve directe	(full way valve) ISI make as specified and	3	Each	
	ying & fixing C.P pillar cock of 15 mm dia quar Make (b) long neck with areator	6	Each	
	ying fixing C.P bib cock of 15 mm dia SCO make	19	Each	
directo (a	ling fixing C.P towel rail complete as ed a)Jaquar make (ii) Continental 600	6	Each	
chrom sona specif	ying fitting & fixing overhead adjustable he plated(C.P) spray shower 15mm dia. Of make with wall flange as directed and ied.(pipes will be measured and paid htely) (d)Hammer shower with arm	6	Each	
Chlor hot ar and b clamp pipe. (A) Ez	ling and fixing Chlorinated Polyvinyle ide (CPVC) pipes having thermal stability for ad cold water supply including all cpvc plain rass threaded fittings i/c fixing the pipe with as at 1.00m spacing. this includes jointing of sposed or in trenches(a) 15mm dia	20.00	Rm.	
(c)25	mm dia	15.00	Rm.	
Total (Including GST) =				