

Price Bid					
Name of Work:- Tower Protection with Concreting & Stone Pitching at Loc No. 11 and Muffling Work at Loc No. 8 and 9 of 220kV Balipara-Sonabil Transmission Line.					
NIT NO: AEGCL/DGM/TTC/TEZ/T-20/2026/326 Date 16/06/2026					
Name of the bidder.....					
Sl. No.	Description of Items	Qty	Unit	Rate(Rs.)	Amount(Rs.)
1	PCC (Muffling) work upto 1.2m from the ground level	8	Per leg		
2	For loc 11: Stone for pitching at the embankments of the sides of the tower legs having an average embankment upto required depth	5.00	cum		
3	Galvanised Polymer coated wire mesh of average width of aperture 1.4mm and nominal dia of wire 0.63mm to anchor the stone pitching at the embankments.	18.10	sqm		
4	Excavation work by mechanical means (Hydraulic excavator)/ manual means in foundation trenches or drains (not exceeding 1.5m in width or 10 sqm on plan), including dressing of sides and ramming of bottoms, lift upto 1.5 m, including getting out the excavated soil and disposal of surplus excavated soils as directed, within a lead of 50 m.	36.96	cum		
5	Steel reinforcement for R.C.C. work including straightening, cutting, bending, placing in position and binding all complete above plinth level. Thermo-Mechanically Treated bars of grade Fe-500D or more.	202.21	kg		
6	Steel Centering and shuttering including strutting, propping etc. and removal of form for Columns, Pillars, Piers, Abutments, Posts and Struts	88.00	sqm		
7	Providing and laying in position specified grade of reinforced cement concrete, excluding the cost of centering, shuttering, finishing and reinforcement - All work up to plinth level : 1:1.5:3 (1 cement : 1.5 coarse sand (zone-III) derived from natural	28.16	cum		
8	20 mm cement plaster of mix : 1:4 (1 cement: 4 fine sand) Beam surface above 4 m level height	100.80	sqm		
9	Providing and fixing double scaffolding system on the exterior side, up to seven story height made with 40 mm dia M.S. tube 1.5 m centre to centre, horizontal & vertical tubes joining with cup & lock system with M.S. tubes or Bamboo with ropes for working platform etc. and maintaining it in a serviceable condition for required duration as approved and removing it there after .The scaffolding system shall be stiffened with bracings, runners, connection with the building etc wherever required for inspection of work at required locations with essential safety features for the workmen etc. complete as per directions and approval of Engineer-in-charge .	98.00	Sqm		
				Total=	
				Add 18% GST=	
				Grand Total=	

Seal and Signature of the bidder