

**PRICE BID**

**Name of Work: Renovation (Plastering, Painting, Tiles & Sanitary ) of Control Room at 132 KV Nalkata GSS**

| SL No.          | Item Description  | Quantity | unit | Rate(Including GST) | Amount |
|-----------------|---|----------|------|---------------------|--------|
| 1               | Repairs to plaster of thickness 12 mm to 20 mm in patches of area 2.5 sq.meters and under, including cutting the patch in proper shape, raking out joints and preparing and plastering the surface of the walls complete, including disposal of rubbish to the dumping ground, all complete as per direction of Engineer-in-Charge.<br>14.1.1<br>With cement mortar 1:4 (1 cement : 4 fine sand)  | 49.275   | Sqm  |                     |        |
| 2               | Providing and applying plaster of paris putty of 2 mm thickness over plastered surface to prepare the surface even and smooth complete.   | 250.82   | Sqm  |                     |        |
| 3               | Finishing with Epoxy paint (two or more coats) at all locations prepared and applied as per manufacturer's specifications including appropriate priming coat, preparation of surface, etc. complete.<br>13.52.2 On concrete work  | 250.82   | Sqm  |                     |        |
| 4               | Dismantling tile work in floors and roofs laid in cement mortar including stacking material within 50 metres lead.<br>15.23.2 For thickness of tiles above 25 mm and up to 40 mm  | 176.38   | Sqm  |                     |        |
| 5               | Precast terrazo tiles 22 mm thick with graded marble chips of size upto 12 mm, laid in floors, and landings, jointed with neat cement slurry mixed with pigment to match the shade of the tiles, including rubbing and polishing complete, on 20 mm thick bed of cement mortar 1:4 (1 cement:4 coarse sand) :<br>11.16.1 Light shade pigment using white cement   | 176.38   | Sqm  |                     |        |
| <b>Sanitary</b> |   |          |      |                     |        |
| 6               | Providing and fixing white vitreous china pedestal type water closet (European type W.C. pan) with seat and lid, 10 litre low level white P.V.C. flushing cistern, including flush pipe, with manually controlled device (handle lever), conforming to IS : 7231, with all fittings and fixtures complete, including cutting and making good the walls and floors wherever required :<br>17.2.1 W.C. pan with ISI marked white solid plastic seat and lid | 1        | Each |                     |        |
| 7               | Providing and fixing wash basin with C.I. brackets, 15 mm C.P. brass pillar taps, 32 mm C.P. brass waste of standard pattern, including painting of fittings and brackets, cutting and making good the walls wherever require:<br>17.7.1 White Vitreous China Wash basin size 630x450 mm with a pair of 15 mm C.P. brass pillar taps  | 1        | Each |                     |        |
| 8               | Providing and fixing brass bib cock of approved quality :<br>18.15.1 15 mm nominal bore   | 2        | Each |                     |        |
| 9               | Providing and fixing C.P. brass shower rose with 15 or 20 mm inlet :<br>18.22.1 100 mm diameter   | 1        | Each |                     |        |
| <b>Total=</b>   |   |          |      |                     |        |