

Price Bid

NIT No.:-AEGCL/DGM/TTC/NLP/T-3/2026-27/02 Date: 18.06.2026

Name of Work: Construction of IB approach road with Inter locking concrete paver block (ICBP) at 132 KV Majuli GSS

1	Granular Sub-base with Well Graded Material (Table 400.1) mix in place method- Construction of granular sub-base by providing well graded material, spreading in uniform layers with motor grader on prepared surface, mixing by mix in place method with rotavator at OMC, and compacting with smooth wheel roller to achieve the desired density, complete as per Technical Specification Clause401. (I) For Grading I Material	(A) By				
			32.69	Cum		
2	Water Bound Macadam Sub-base/base Grading 3 Using stone screening Type-B 11.2 mm for Gr.III Providing, laying, spreading and compacting stone aggregates of specific sizes to water bound macadam specification including spreading in uniform thickness, hand packing, rolling with smooth wheel roller 80-100 kN in stages to proper grade and camber, applying and brooming, stone screening/binding materials to fill-up the interstices of coarse aggregate, watering and compacting to the required density grading 2 as per Technical Specification Clause 405.	WBM				
		(A) By manual Means	16.34	Cum		
3	Inter locking concrete Block pavement (A) Interlocking pavement block (i) Providing and laying interlocking concrete block pavement with M40 grade of concrete blocks having thickness 80mm as per technical specification clause 1504 including carriage (a)(including Edge block/Edge restraints.					
			217.90	Sqm		
4	Providing and laying in position cement concrete of specified gradeexcluding the cost of centering and shuttering - All work up to plinthlevel : 1:4:8 (1 Cement : 4 coarse sand (zone-III) derived from naturalsources : 8 graded stone aggregate 40 mm nominal sizederived from natural sources)					
			9.63	Cum		
5	Steel work in built up tubular (round, square or rectangular hollow tubes etc.) trusses etc., including cutting, hoisting, fixing in position and applying a priming coat of approved steel primer, including welding and bolted with special shaped washers etc. complete. Hot finished welded type tubes 50 mm dia pipe of 3.65mm thickness @ 5.1 Kg/m					
			280.50	Kg		
6	Providing and fixing on wall face unplasticised Rigid PVC rain water pipes conforming to IS : 13592 Type A, including jointing with seal ring conforming to IS : 5382, leaving 10 mm gap for thermal expansion, (i) Single socketed pipes. 110 mm diameter					
			80.00	m		
7	Providing and fixing on wall face unplasticised - PVC moulded fittings/accessories for unplasticised Rigid PVC rain water pipes conforming to IS 13592 Type A, including jointing with seal ring conforming to IS : 5382, leaving 10 mm gap for thermal expansion. Coupler 110mm					
			15.00	Each		
Sum Total, Rs. =						
Add CGST (9.00%), Rs. =						
Add SGST (9.00%), Rs. =						
Grand Total, Rs. =						