## Price Bid

Name of Work:Renovation (Electrification, Sanitary, Tiles, Door, Window & ceiling) of IB at 132KV GSS, Dhemaji

SL No	Item Description	Quantity	Unit	Rate (Rs)	Amount (Rs)Inclusive of all taxes
1	Dismantling doors, windows and clerestory windows (steel or wood) shutter including chowkhats, architrave, holdfasts etc. complete and stacking within 50 metres lead:  15.12.1 Of area 3 sq. metres and below  Total = 54	54	Each		
2	Providing wood work in frames of doors, windows, clerestory windows and other frames, wrought framed and fixed in position with hold fast lugs or with dash fasteners of required dia & length (hold fast lugs or dash fastener shall be paid for separately).  9.1.3 Kiln seasoned and chemically treated hollock wood  Total = 1.053	1.053	Cum		
3	Providing and fixing panelled or panelled and glazed shutters for doors, windows and clerestory windows, fixing with butt hinges of required size with necessary screws, excluding panelling which will be paid for separately, all complete as per direction of Engineer-in-charge. (Note:-Butt hinges and necessary screws shall be paid separately)  9.5.2 Kiln seasoned and chemically treated hollock wood  9.5.2.2 30 mm thick shutters  Total = 50.58	50.58	Sqm		
4	Dismantling tile work in floors and roofs laid in cement mortar including stacking material within 50 metres lead.  15.23.2  For thickness of tiles above 25 mm and up to 40 mm  Total = 90.33		Sqm		
5	Precast terrazo tiles 22 mm thick with graded marble chips of size upto 12 mm, laid in floors, and landings, jointed with neat cement slurry mixed with pigment to match the shade of the tiles, including rubbing and polishing complete, on 20 mm thick bed of cement mortar 1:4 (1 cement:4 coarse sand): 11.16.1 Light shade pigment using white cement		·		
6	Area as per SI No. 4 = 90.33  Providing wood work in frames of false ceiling, partitions etc. sawn and fixed in position with necessary stainless steel screws etc.  9.3.2 Kiln seasoned and chemically treated hollock wood	90.33	Sqm		

	Total = 0.967	0.967	Cum	
	Providing and fixing insulating board ceiling of approved quality with necessary nails etc. complete			
7	(frame work to be paid separately): 12.24.2			
	White face insulating board 12.24.2.1 12			
	mm thick			
	Total = 120.86	120.86	Sqm	
	Sanitary and Electrification			
8	Providing and fixing white vitreous china pedestal type water closet (European type W.C. pan) with seat			
	and lid, 10 litre low level white P.V.C. flushing cistern, including flush pipe, with manually controlled			
	device (handle lever), conforming to IS: 7231, with all fittings and fixtures complete, including cutting			
	and making good the walls and floors wherever required: 17.2.1 W.C. pan with ISI marked white solid plastic seat and lid			
	solid plastic seat and hu			
	Total = 2	2	Each	
	Providing and fixing water closet squatting pan (Indian type W.C. pan ) with 100 mm sand cast Iron P or			
	S trap, 10 litre low level white P.V.C. flushing cistern, including flush pipe, with manually controlled			
	device (handle lever) conforming to IS: 7231, with all fittings and fixtures complete, including cutting			
9	and making good the walls and floors wherever required: 17.1.1 White Vitreous china Orissa pattern			
	W.C. pan of size 580x440 mm with integral type foot rests			
	Total = 1	. 1	Each	
	Providing and fixing wash basin with C.I. brackets, 15 mm C.P. brass pillar taps, 32 mm C.P. brass waste			
	of standard pattern, including painting of fittings and brackets, cutting and making good the walls			
10	wherever require: 17.7.1 White			
	Vitreous China Wash basin size 630x450 mm with a pair of 15 mm C.P. brass pillar taps			
		1	To ala	
	Total = 1 Providing and fixing mirror of superior glass (of approved quality) and of required shape and size with	. 1	Each	
11	plastic moulded frame of approved make and shade with 6 mm thick hard board backing:			
	17.32.3 Oval shape 450x350 mm (outer dimensions)			
	(			
	Total = 3	3	Each	
	Providing and fixing brass bib cock of approved quality:	, ,	Lucii	
12	18.15.1 15 mm nominal bore			
	Total = 5	5 5	Each	
	Total –	,	Lacii	

13	Providing and fixing C.P. brass shower rose with 15 or 20 mm inlet: 18.22.1 100 mm diameter					
	Total = 3	3	Each			
14	Wiring for light point/ fan point/ exhaust fan point/ call bell point with 1.5 sq.mm FRLS PVC insulated copper conductor single core cable in surface / recessed steel conduit, with piano type switch, phenolic laminated sheet, suitable size MS box and earthing the point with 1.5 sq.mm FRLS PVC insulated copper conductor single core cable etc. as required.  1.1.3  Group C  Total = 7	7	Each			
Total=						
Say Rs.=						