

REVISED PRICE BID

SL. No.	Item Description	Unit	Qty.	Rate	Amount
1	Preparation and consolidation of subgrade with power road roller of 8to12-tonne capacity after excavating earth to an average of 22.5cm depth,dressing to camber and consolidating with road roller including making good the undulations etc. and re-rolling the sub grade and disposal of surplus earthwith lead upto 50 metres.	Sq.m.	500.00		
2	Supplying and stacking at site.16.3.6 Stone screening 13.2 mm nominal size (Type A)	Cum.	50.00		
3	Laying,spreading and compacting stone aggregate of specified sizes to WBM specifications in uniform thickness,handpicking,rolling with 3wheeled road/vibratoryroller 8-10tonne capacity in stages to proper grade and camber, applying and brooming requisite type of screening/binding material to fillup in terstices of coarse aggregate,watering and compacting to the required density	Cum.	50.00		
4	Providing and applying tack coat using hot straight run bitumen of grade VG - 10, including heating the bitumen, spraying the bitumen with mechanically operated spray unit fitted on bitumen boiler, cleaning and preparing the existing road surface as per specifications :On W.B.M. @ 0.75 Kg / sqm	sqm	500.00		
	On bituminous surface @ 0.50 Kg / sqm	sqm	500.00		

5	<p>Providing and laying Dense Graded Bituminous Macadam using crushed stone aggregates of specified grading, premixed with bituminous binder and filler, transporting the hot mix to work site by tippers, laying with paver finisher equipped with electronic sensor to the required grade, level and alignment and rolling with smooth wheeled, vibratory and tandem rollers as per specifications to achieve the desired compaction and density, complete as per specifications and directions of Engineer-in-Charge.</p> <p>50 to 100 mm average compacted thickness with bitumen of grade VG-30 @ 5% (percentage by weight of total mix) and lime filler @ 2% (percentage by weight of Aggregate) prepared in Drum Type Hot Mix Plant of 60-90 TPH capacity.</p>	Cum.	52.50		
6	<p>Providing and laying seal coat over prepared surface of road with bitumen heated in bitumen boiler fitted with the spray set spraying using 98 kg of bitumen of grade VG - 10 and blinding surface with 0.90 cum of stone aggregate of 6.7 mm size (Passing 11.2 mm sieve and retained on 2.36 mm sieve) per 100 sqm of road surface, including rolling and finishing with power road roller all complete. Note: Seal coat items to be operated only with the prior approval of chief Engineer concerned.</p>	sqm	500.00		
7	<p>Providing and laying in position cement concrete of specified grade excluding the cost of centering and shuttering - All work up to plinth level :</p> <p>1:1½:3 (1 Cement: 1½ coarse sand (zone-III) derived from natural sources : 3 graded stone aggregate 20 mm nominal size derived from natural sources) cum</p>	Cum.	6.00		
8	<p>Earthwork in excavation by mechanical means (Hydraulic excavator) / manual means over areas (exceeding 30 cm in depth, 1.5 m in width as well as 10 sqm on plan) including getting out and disposal of excavated earth lead up to 50 m and lift up to 1.5 m, as directed by Engineer-in charge. 2.6.1. All kinds of soil</p>	Cum.	40.00		

9	Providing and laying in position cement concrete of specified grade excluding the cost of centering and shuttering - All work up to plinth level 1:3:6 (1 Cement: 3 coarse sand (zone-1) derived from natural sources: 6 grade stone aggregate 20 mm nominal size derived from natural sources)	Cum.	6.00		
10	Steel reinforcement for R.C.C. work including straightening, cutting, bending, placing in position and binding all complete upto plinth level 5.22.6 Thermo-Mechanically Treated bars of grade Fe-500D or more.	kg.	1034.997		
11	Centering and shuttering including strutting, propping etc. and removal of form for 5.9.1 Foundations, footings, bases of columns, etc. for mass concrete	sqm	120.74		
12	Providing and laying in position specified grade of reinforced cement concrete, excluding the cost of centering, shuttering, finishing and reinforcement - All work up to plinth level : 1:1.5:3 (1 cement: 1.5 coarse sand (zone-III) derived from natural sources: 3 grade stone aggregate 20 mm nominal size derived from natural sources)	Cum.	12.00		
13	Supplying at site RCC pipe 450 mm dia NP-3 spigot	Rm	9.00		
14	Supplying at site R.C.C. collars NP2 class 450 mm dia	Each	2		
15	Labour Charge for placing the RCC pipe in existing RCC drain including joining the pipes with Collars etc. complete as per the direction of Engineer In-Charge. (Skilled Labour)	Man-Days	10.00		
			Sub Total:(A)	=	
			18% GST on (A):(B)	=	
			Grand Total(A)+(B)	=	
			Say	=	
In Words					