

Price Bid

NIT No. AEGCL/DGM/TTC/NLP/T-03/2025-26/73 Date:- 29.08.2025

Name of Work: (1) Renovation of Type-V(1) Quarter at 132kV Gohpur GSS .

Sl. No	Item Description	Qty.	unit	Rate	Amount
1	Dismantling roofing including ridges, hips, valleys and gutters etc., and stacking the material within 50 metres lead of: G.S. Sheet	12.00	Sqm		
2	Providing corrugated G.S. sheet roofing including vertical / curved surface fixed with polymer coated J or L hooks, bolts and nuts 8 mm diameter with bitumen and G.I. limpet washers or with G.I. limpet washers filled with white lead, including a coat of approved steel primer and two coats of approved paint on overlapping of sheets complete (up to any pitch in horizontal/ vertical or curved surfaces), excluding the cost of purlins, rafters and trusses and including cutting to size and shape wherever required. 0.63 mm thick with zinc coating not less than 275 gm/ m ²	12.00	Sqm		
3	Providing and fixing precoated galvanised steel sheet roofing accessories 0.50 mm (+0.05 %) total coated thickness, Zinc coating 120 grams per sqm as per IS: 277, in 240 mpa steel grade, 5-7 microns epoxy primer on both side of the sheet and polyester top coat 15-18 microns using self drilling/ self tapping screws complete : Barge board (Upto 300 mm)	22.00	meter		
4	Demolishing brick work manually/ by mechanical means including stacking of serviceable material and disposal of unserviceable material within 50 metres lead as per direction of Engineer-in-charge. In cement mortar	0.936	cum		
5	Brick work with common burnt clay machine moulded perforated bricks of class designation 12.5 conforming to IS: 2222 in superstructure above plinth level up to floor five level in cement mortar 1:6 (1 cement : 6 coarse sand) : With Modular bricks	1.751126	cum		
6	Providing and fixing panelled or panelled and glazed shutters for doors, windows and clerestory windows, fixing with butt hinges of required size with necessary screws, excluding panelling which will be paid for separately, all complete as per direction of Engineer-in-charge. (Note:-Butt hinges and necessary screws shall be paid separately) Kiln seasoned and chemically treated hollock wood 30 mm thick shutters	1.1875	Sqm		
7	15 mm cement plaster on the rough side of single or half brick wall of mix : 1:4 (1 cement: 4 fine sand)	8.4625	sqm		
8	12 mm cement plaster of mix : 1:4 (1 cement: 4 fine sand)	22.7825	sqm		
9	Finishing with Deluxe Multi surface paint system for interiors and exteriors using Primer as per manufacturers specifications : Two or more coats applied on walls @ 1.25 ltr/10 sqm over and including one coat of Special primer applied @ 0.75 ltr /10 sqm	28.1605	Sqm		
Name of Work: (2) Newly Construction of Septic Tank(I) for Guest House at 132 kV Gohpur GSS					
1	Earth work in excavation by mechanical means (Hydraulic excavator)/ manual means over areas (exceeding 30 cm in depth, 1.5 m in width as well as 10 sqm on plan) including getting out and disposal of excavated earth lead upto 50 m and lift upto 1.5 m, as directed by Engineer-in- charge. All kind of soil	25.97	Cum		

2	Supplyin and stacking at site Over burnt (jhamma) Brick aggregates of 120 mm to 40 mm	1.00	Cum		
3	Providing and laying in position cement concrete of specified grade excluding the cost of centering and shuttering - All work up to plinth level : 1:3:6 (1 Cement: 3 coarse sand (zone-III) derived from natural sources: 6 graded stone aggregate 40 mm nominal size derived from natural sources)	1.36	Cum		
4	Brick work with common burnt clay modular bricks of class designation 7.5 in foundation and plinth in: Cement Mortar 1:6 (1. cement: 6 coarse sand) Long Wall = 2.84 Short Wall = 1.67 Scum Board = 0.41 Buffle Wall = 0.40 <div>Total = 5.32</div>	5.32	cum		
5	12 mm cement plaster of mix: 13.1.2 1:6 (1 cement : 6 fine sand) A. Inside the Tank i. Long Wall = 13.20 ii. Short Wall = 8.80 B. Floor = 6.00 C. All around Scum Board = 8.20 D. All around Buffle Wall = 8.08 <div>Total = 44.28</div>	44.28	Sqm		
6	Excavating, supplying and filling of local earth (including royalty) by mechanical transport upto a lead of 5km also including ramming and watering of the earth in layers not exceeding 20 cm in trenches, plinth, sides of foundation etc. complete for all lift.	4.167	Cum		
7	Steel reinforcement for R.C.C. work including straightening, cutting, bending, placing in position and binding all complete upto plinth level. Thermo-Mechanically Treated bars of grade Fe-500D or more. TATA Steel	57.504	Kg		
8	Centering and shuttering including strutting, propping etc. and removal of form for Foundations, footings, bases of columns, etc. for mass concrete	8.160	sqm		
9	Providing and laying in position specified grade of reinforced cement concrete, excluding the cost of centering, shuttering, finishing and reinforcement - All work up to plinth level : 1:2:4 (1 cement : 1.5 coarse sand (zone-III) derived from natural sources : 3 graded stone aggregate 20 mm nominal size derived from natural sources)	0.816	Cum		
10	Providing and fixing on wall face unplasticised - PVC moulded fittings/accessories for unplasticised Rigid PVC rain water pipes conforming to IS 13592 Type A, including jointing with seal ring conforming to IS : 5382, leaving 10 mm gap for thermal expansion. Coupler 110mm 5.00	5.00	Each		
Name of Work: (2) Newly Construction of Septic Tank(II) for Guest House at 132 kV Gohpur GSS					
1	Earth work in excavation by mechanical means (Hydraulic excavator)/ manual means over areas (exceeding 30 cm in depth, 1.5 m in width as well as 10 sqm on plan) including getting out and disposal of excavated earth lead upto 50 m and lift upto 1.5 m, as directed by Engineer-in- charge. All kind of soil	25.97	Cum		
2	Supplyin and stacking at site Over burnt (jhamma) Brick aggregates of 120 mm to 40 mm	1.00	Cum		

3	Providing and laying in position cement concrete of specified grade excluding the cost of centering and shuttering - All work up to plinth level : 1:3:6 (1 Cement: 3 coarse sand (zone-III) derived from natural sources: 6 graded stone aggregate 40 mm nominal size derived from natural sources)	1.36	Cum		
4	Brick work with common burnt clay modular bricks of class designation 7.5 in foundation and plinth in: Cement Mortar 1:6 (1. cement: 6 coarse sand) Long Wall = 2.84 Short Wall = 1.67 Scum Board = 0.41 Buffle Wall = 0.40 <div style="text-align: right;">Total = 5.32</div>	5.32	cum		
5	12 mm cement plaster of mix: 1:6 (1 cement : 6 fine sand) A. Inside the Tank i. Long Wall = 13.20 ii. Short Wall = 8.80 B. Floor = 6.00 C. All around Scum Board = 8.20 D. All around Buffle Wall = 8.08 <div style="text-align: right;">Total = 44.28</div>	44.28	Sqm		
6	Excavating, supplying and filling of local earth (including royalty) by mechanical transport upto a lead of 5km also including ramming and watering of the earth in layers not exceeding 20 cm in trenches, plinth, sides of foundation etc. complete for all lift.	4.167	Cum		
7	Steel reinforcement for R.C.C. work including straightening, cutting, bending, placing in position and binding all complete upto plinth level. Thermo-Mechanically Treated bars of grade Fe-500D or more. TATA Steel	57.504	Kg		
8	Centering and shuttering including strutting, propping etc. and removal of form for Foundations, footings, bases of columns, etc. for mass concrete	8.160	sqm		
9	Providing and laying in position specified grade of reinforced cement concrete, excluding the cost of centering, shuttering, finishing and reinforcement - All work up to plinth level : 1:2:4 (1 cement : 1.5 coarse sand (zone-III) derived from natural sources : 3 graded stone aggregate 20 mm nominal size derived from natural sources)	0.816	Cum		
10	Providing and fixing on wall face unplasticised - PVC moulded fittings/accessories for unplasticised Rigid PVC rain water pipes conforming to IS 13592 Type A, including jointing with seal ring conforming to IS : 5382, leaving 10 mm gap for thermal expansion. Coupler 110mm 5.00	5.00	Each		

Sum Total, Rs.=

Add CGST (09.00%), Rs.=

Add SGST (09.00%), Rs.=

Grand Total, Rs.=

Amount in Word:-